



ES 1.5ATD



Pitch:3.5 mm



45 a nglcd connection

IEC 数据	刚性导线 (mm ²)	柔性导线 (mm ²)	AWG	I (A)	U (V)
连接数据	0.5-1.5	0.5-1.5	20-16	2	250
绝缘材料组别				I	
污染等级				3	2
过电压类别				III	II
额定电压(V)				250	400
额定冲击电压(KV)				4	
绝缘材料/阻燃等级 UL 94				PA/V0	
螺钉/扭矩(-Nm)				\	
剥线长度(mm)				8	
线路板孔径(mm)				Ø1.0	
引脚尺寸 (mm)				0.4X0.8	

UL 数据

额定电压(V)/电流(A)	300/2
压线范围(AWG)	24-16


IEC	Rigid (mm ²)	flexible (mm ²)	AWG	I (A)	U (V)
Connection data	0.5-1.5	0.5-1.5	20-16	2	250
Insulating Material Group				I	
Pollution degree				3	2
Overvoltage Category				III	II
Rate Voltage(V)				250	400
Rate impulse Voltage(KV)				4	
Insulating material/Inflammability Class				PA/V0	
Screw/Torque(-Nm)				\	
Stripping length(mm)				8	
PCB Hole Diameter(mm)				Ø1.0	
Pin Dimensions(mm)				0.4X0.8	

UL Technical Data


Rate Voltage(V)/Current(A)	300/2
Wire Range(AWG)	24-16

位数/No. of positions	订货型号/Order No.
2	ES 1.5ATD-2-3.5
...	...
24	ES 1.5ATD-24-3.5

ES 1.5AT



Pitch:3.5 mm



45 a nglcd connection

IEC 数据	刚性导线 (mm ²)	柔性导线 (mm ²)	AWG	I (A)	U (V)
连接数据	0.5-1.5	0.5-1.5	20-16	2	250
绝缘材料组别				I	
污染等级				3	2
过电压类别				III	II
额定电压(V)				250	400
额定冲击电压(KV)				4	
绝缘材料/阻燃等级 UL 94				PA/V0	
螺钉/扭矩(-Nm)				\	
剥线长度(mm)				8	
线路板孔径(mm)				Ø1.0	
引脚尺寸 (mm)				0.4X0.8	

UL 数据

额定电压(V)/电流(A)	300/2
压线范围(AWG)	24-16

IEC	Rigid (mm ²)	flexible (mm ²)	AWG	I (A)	U (V)
Connection data	0.5-1.5	0.5-1.5	20-16	2	250
Insulating Material Group				I	
Pollution degree				3	2
Overvoltage Category				III	II
Rate Voltage(V)				250	400
Rate impulse Voltage(KV)				4	
Insulating material/Inflammability Class				PA/V0	
Screw/Torque(-Nm)				\	
Stripping length(mm)				8	
PCB Hole Diameter(mm)				Ø1.0	
Pin Dimensions(mm)				0.4X0.8	

UL Technical Data

Rate Voltage(V)/Current(A)	300/2
Wire Range(AWG)	24-16

位数/No. of positions	订货型号/Order No.
2	ES 1.5AT-2-3.5
...	...
24	ES 1.5AT-24-3.5